


product name		Production location
Aragon red-brown multi coloured ZV/MA(spacer)	A4-12G	Spijk
Format		
Moulding method		Mould
WF85: 206 x 51 x 85 mm DF85: 206 x 67 x 85 mm		Between batches the average size and color may slightly differ.
Essential Characteristics - EN1344		
CE		
Reaction to fire	Klasse A1	Category
External fire performance	NPD	
Dangerous substances	NL-BSB	
Transverse breaking load	T4	Category
Slip and skid resistance USRV	U3	Category
Thermal Property	NPD	Value according EN1745, Annex A 90%
Freeze/thaw resistance	FP100	Category
Durability of Slip and skid resistance	U2	Category
Other Characteristics - EN1344 & BRL 2360		
Quality Class	A4-12G	Category
Tolerances of the mean value	$\leq 0,4 \sqrt{\text{dimensions}}$	
Range	R1	Category
Water absorption	$\leq 5\% \text{ m/md}$	
Abrasion resistance	A2	Category
Acid resistance	C	Category
		
Storage & handling		Cutting
<ul style="list-style-type: none"> - Stock pavers on a clean surface and cover them - Blend from different pavers (pack) at the same time - Do not clean fresh masonry with hydrochloric acid 		Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3).