


product name		Production location	
Corsica ochre yellow multi coloured ZV/MA(spacer)		A4-12G	Spijk
Format			
Moulding method		Mould	
WF85: 206 x 51 x 85 mm DF85: 206 x 67 x 85 mm		Between batches the average size and color may slightly differ.	
Essential Characteristics - EN1344			
CE			
Reaction to fire	Klasse A1	Category	
External fire performance	NPD		
Dangerous substances	NL-BSB		
Transverse breaking load	T4	Category	
Slip and skid resistance USRV	U3	Category	
Thermal Property	NPD	Value according EN1745, Annex A 90%	
Freeze/thaw resistance	FP100	Category	
Durability of Slip and skid resistance	U2	Category	
Other Characteristics - EN1344 & BRL 2360			
Quality Class	A4-12G	Category	
Tolerances of the mean value	$\leq 0,4 \sqrt{\text{dimensions}}$		
Range	R1	Category	
Water absorption	$\leq 5\% \text{ m/md}$		
Abrasion resistance	A2	Category	
Acid resistance	C	Category	
			
Storage & handling		Cutting	
<ul style="list-style-type: none"> - Stock pavers on a clean surface and cover them - Blend from different pavers (pack) at the same time - Do not clean fresh masonry with hydrochloric acid 		Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3).	