


product name		Production location	
Görlitz Geschaafd ZV/ZA		NPD	Oberlausitz
Format			
Moulding method		Wirecut	
KF71: 206 x 102 x 71 mm KF52: 206 x 102 x 52 mm		Between batches the average size and color may slightly differ.	
Essential Characteristics - EN1344			
CE			
Reaction to fire	A1	Category	
External fire performance	NPD		
Dangerous substances	NPD		
Transverse breaking load	T4	Category	
Slip and skid resistance USRV	U3	Category	
Thermal Property	NPD	Value according EN1745, Annex A 90%	
Freeze/thaw resistance	FP100	Category	
Durability of Slip and skid resistance	NPD	Category	
Other Characteristics - EN1344 & BRL 2360			
Quality Class	NPD	Category	
Tolerances of the mean value	$\leq 0,4 \sqrt{\text{dimensions}}$		
Range	R1	Category	
Water absorption	$\leq 6\% \text{ m/md}$		
Abrasion resistance	NPD	Category	
Acid resistance	NPD	Category	
			
Storage & handling		Cutting	
<ul style="list-style-type: none"> - Stock pavers on a clean surface and cover them - Blend from different pavers (pack) at the same time - Do not clean fresh masonry with hydrochloric acid 		Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3).	